

## OMNITRONIC GEQ-2150 Equalizer 2x15-Band

2 x graphic equalizer 15-band

Art. No.: 10355522

GTIN: 4026397522822



**List price: 148.75 €**

incl. 19% VAT.

### Features:

- 2-channel version, 2 x 15 frequency controls with 2/3 octave steps
- Short sliding frequency controls with center click
- EQ gain switchable  $\pm 6$  dB to  $\pm 12$  dB
- Separate level control per channel
- Bypass switch allows instant comparison of original sound with processed sound
- Inputs and outputs via 6.3 mm jack sockets and XLR sockets
- (19") 48.3 cm rack installation 1 U
- For application areas such as: Installation; clubs/dancing school; stage; homerecording and studios; band/rehearsal room

#### Package contents

- 1 x user manual, 1 x power cord, 1 x device

### Logistic

EAN / GTIN: 4026397522822

Weight: 2,87 kg

Length: 0.54 m

Width: 0.24 m

Height: 0.10 m

### Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	13 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	20 - 20000 Hz
S/N ratio:	>96 dB

THD:	<0,05 % at 1 kHz
Impedance:	Input: 20 kOhm , bal. Input: 15 kOhm , unbal. Output: 300 kOhm , bal. Output: 150 kOhm , unbal.
Gain:	Output: - ? to + 6 dB
Control range:	±6dB, ±12dB, switchable
Control elements:	Groundlift selector, bypass/terminating resistor switch
Status LED:	Power, clip
Connections:	Input: line via 2 x 3-pin XLR Input: line via 2 x 6.3 mm plug (unbal.) Output: line via 2 x 3-pin XLR Output: line via 2 x 6.3 mm plug (unbal.)
Equalizer:	Master: 2 x graphic equalizer 15-band Centre frequency: ISO standard, 2/3 octave, 25/40/63/100/160/250/400/630 Hz, 1/1,6/2,5/4/6,3/10/16 kHz
Max. level:	Input: +24 dBu, bal. Input: +18 dBu, unbal. Output: +24 dBu, bal. Output: +18 dBu, unbal.
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48,3 cm Depth: 22 cm Height: 4,45 cm
Weight:	2,40 kg