

INTUSONIC PAA42+ Dual Output Stereo Media Preampfier

19" preamplifier with media player, DAB+, wireless audio, IR remote and RS485 control option

Art. No.: 12604186

GTIN: 5060502923523



List price: on demand €

incl. 19% VAT.

Description:

The INTUWORX PAA42+ is a media preamp/mixer which combines a 6-input stereo preamplifier with 2 microphone inputs and an internal media player. The microphone section features phantom power and high-pass filters, and allows automatic attenuation of the music signal (talkover/priority), making this unit a popular choice with fitness instructors. The internal media player offers USB replay, DAB+ and FM reception, LINKOUSTIC 5.0 wireless audio link and an IR remote control. The two master outputs with fire evacuation facilities can work mono or stereo, and the main output can be remotely controlled via RS485 with the optional VRE11 wall panel. The second output also offers the direct choice of selected inputs as sources, making it effectively a zone output. A dedicated priority line input for a chime or message player, as well as one of the stereo inputs being balanced for long cable runs, complete this unit.

Logistic

EAN / GTIN: 5060502923523

Weight: 3,90 kg

Length: 0.54 m

Width: 0.33 m

Height: 0.10 m

Features:

- Control via IR remote control; RS 485; LINKOUSTIC 4.2 Wireless Audio Link
- 2.4 GHz license-free worldwide
- LCD display
- (19") 48.3 cm rack installation
- Desktop console housing
- For application areas such as: Installation; restaurants, bars and hotels
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x user manual, 1 x device, 1 x power cord, 1 x plug (male), 4 x foot, 1 x antenna, 1 x adapter, 1 x remote control, 1 x battery

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	Max. 12 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC (M) power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 0,5 A fuse replaceable
Frequency range:	20 - 20000 Hz
S/N ratio:	>102 dB
THD:	<0,015 % at 1 kHz
Control:	IR remote control; RS 485; LINKOUSTIC 4.2 Wireless Audio Link
Bluetooth:	Version: 5,0
Bluetooth device name:	LINKOUSTIC
Audio player:	USB + Bluetooth; DAB+; FM tuner
Frequency band:	2.4 GHz
Crosstalk:	>63 dB
Display type:	LCD display
Control elements:	Power switch, level control, regular talkover, phantom power switch
Connections:	Input: line via 3 x stereo RCA Input: line via 2 x 6.3-mm-jack (bal.) Input: microphone via 2 x 6.3-mm-jack (bal.) Input: microphone via screw plug-in terminal Output: master via screw plug-in terminal Output: zones via screw plug-in terminal Output: rec. via stereo RCA Mute function via screw plug-in terminal RS 485 via 1 x RJ-45 (F) mounting version Emergency via screw plug-in terminal Priority via screw plug-in terminal Antenna via 2 x SMA (F) mounting version
Music format:	MP3, WAV; FLAC, APE
Available storage media:	USB devices max. 64GB (FAT 32)
USB port:	USB 2.0, type B
Color:	Black
Housing design:	(19") 48.3 cm rack installation Desktop console housing
Dimensions:	Width: 48,3 cm Depth: 25 cm Height: 4,4 cm
Weight:	3,35 kg