eurolite®

EUROLITE Set 4x AKKU Mini UP-4 QCL Spot MK2 + Soft bag

Art. No.: 20001031 GTIN: 4026397739510







List price: 534.31 €

incl. 19% VAT.

Features:

EUROLITE AKKU Mini UP-4 QCL Spot MK2

Mini battery-powered uplight with RGBW LEDs and IR remote control

- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- 4 powerful LEDs 4 W 4in1 QCL RGBW (homogenous color mix)
- Color change adjustable; color fade adjustable; color blend stepless
- Strobe effect; uplight effect
- Direct color selection for 10 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; sound to light via microphone
- Flicker-free
- With a beam angle of 18°
- 4 digit 7-segment LED display
- Integrated automatic charging of the battery and status indicator
- Silent operation
- Application possibility: Standing
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental

Package contents

- 1 x device, 1 x user manual, 1 x remote control, 1 x battery, 1 x USB cable

EUROLITE Softbag for 4x AKKU Mini UP-4 QCL Spot MK2

Nylon transport bag

- With 4 device compartments

Logistic

EAN / GTIN: 4026397739510 Weight: 4,50 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m

- With accessory compartment
- High-quality workmanship with nylon , black
- Interior with foam padding
- 2 carrying straps

Technical specifications:

Weight:

4,03 kg

EUROLITE AKKU Mini UP-4 QCL Spot MK2

used Recharging time 5h Lamp type: LED lamp LED type: 4 x 4 W 4in1 QCL RGBW (homogenous color mix) Flash rate: 1 - 20 Hz Cooling: Passive convection cooling	Power supply:	5 V
Power connection: Battery/battery pack Mains input via USB C (W) mounting version Battery pack type: 3 x lithium ion 3,6 V, 2600 mAh, 9,36 Wh Battery pack: Battery operation up to 9h depending on program used Recharging time 5h Lamp type: LED lamp LED type: 4 x 4 W 4in1 QCL RGBW (homogenous color mix) Flash rate: 1 - 20 Hz Cooling: Passive convection cooling Control: IR remote control; stand-alone; sound to light via microphone Projection: Flicker-free Beam angle: 18° Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Weight: 0,73 kg 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	IP classification:	IP20
Mains input via USB C (W) mounting version Battery pack type: 3 x lithium ion 3,6 V, 2600 mAh, 9,36 Wh Battery pack: Battery operation up to 9h depending on progran used Recharging time 5h LED lamp LED type: 4 x 4 W 4in1 QCL RGBW (homogenous color mix) Flash rate: 1 - 20 Hz Cooling: Passive convection cooling Control: IR remote control; stand-alone; sound to light via microphone Projection: Flicker-free Beam angle: 18° Beam angle (1/12 peak): 18° Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Protection class:	Protection class III
Battery pack: Battery operation up to 9h depending on program used Recharging time 5h Lamp type: LED lamp LED type: 4 x 4 W 4in1 QCL RGBW (homogenous color mix) Flash rate: 1 - 20 Hz Cooling: Passive convection cooling Control: IR remote control; stand-alone; sound to light via microphone Projection: Flicker-free Beam angle: 18° Beam angle (1/2 peak): 18° Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Power connection:	
used Recharging time 5h Lamp type: LED lamp LED type: 4 x 4 W 4in1 QCL RGBW (homogenous color mix) Flash rate: 1 - 20 Hz Cooling: Passive convection cooling Control: IR remote control; stand-alone; sound to light via microphone Projection: Flicker-free Beam angle: 18° Beam angle (1/2 peak): 18° Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Battery pack type:	3 x lithium ion 3,6 V, 2600 mAh, 9,36 Wh
Lamp type: LED lamp LED type: 4 x 4 W 4in1 QCL RGBW (homogenous color mix) Flash rate: 1 - 20 Hz Cooling: Passive convection cooling Control: IR remote control; stand-alone; sound to light via microphone Projection: Flicker-free Beam angle: 18° Beam angle (1/2 peak): 18° Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Battery pack:	Battery operation up to 9h depending on program used
LED type: 4 x 4 W 4in1 QCL RGBW (homogenous color mix) Flash rate: 1 - 20 Hz Cooling: Passive convection cooling Control: IR remote control; stand-alone; sound to light via microphone Projection: Flicker-free Beam angle: 18° Beam angle (1/2 peak): 18° Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:		Recharging time 5h
mix) Flash rate: 1 - 20 Hz Cooling: Passive convection cooling Control: IR remote control; stand-alone; sound to light via microphone Projection: Flicker-free Beam angle: 18° Beam angle (1/2 peak): 18° Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Lamp type:	LED lamp
Cooling: Passive convection cooling Control: IR remote control; stand-alone; sound to light via microphone Projection: Flicker-free Beam angle: 18° Beam angle (1/2 peak): 18° Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	LED type:	
Control: IR remote control; stand-alone; sound to light via microphone Projection: Flicker-free Beam angle: 18° Beam angle (1/2 peak): 18° Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Flash rate:	1 - 20 Hz
microphone Projection: Flicker-free Beam angle: 18° Beam angle (1/2 peak): 18° Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Width: 11 cm Height: 12 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Cooling:	Passive convection cooling
Beam angle: 18° Beam angle (1/2 peak): 18° Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Width: 11 cm Height: 12 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Control:	IR remote control; stand-alone; sound to light via microphone
Beam angle (1/2 peak): 18° Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Width: 11 cm Height: 12 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Projection:	Flicker-free
Beam angle (1/10 peak): 38° Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Width: 11 cm Height: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Beam angle:	
Housing color: Black Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Width: 11 cm Height: 12 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Beam angle (1/2 peak):	
Display type: 4 digit 7-segment LED display Dimensions: Length: 11 cm Width: 11 cm Height: 12 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product:	Beam angle (1/10 peak):	
Dimensions: Length: 11 cm Width: 11 cm Height: 12 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Housing color:	Black
Width: 11 cm Height: 12 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Display type:	4 digit 7-segment LED display
Height: 12 cm Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Dimensions:	Length: 11 cm
Weight: 0,73 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination		
Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination		Height: 12 cm
Legal specifications Special product: Not designed for household room illumination	Weight:	0,73 kg
Special product: Not designed for household room illumination	Noise classification:	Class 0 (no noise at all)
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting

EUROLITE Softbag for 4x AKKU Mini UP-4 QCL Spot MK2

Carrying strap:	2 pc/pcs
Material:	Nylon, water repellent

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Color:	Black	
Device compartment:	11 cm x 11 cm x 8 cm	
Dimensions:	Length: 35,5 cm	
	Depth: 29 cm	
	Height: 10 cm	
Weight:	0,39 kg	