eurolite®

EUROLITE Set 4x LED CLS-18 QCL RGB/WW 18x7W + Flightcase with wheels No.: 20001036 GTIN: 4026397733082







List price: 1783.81 €

incl. 19% VAT.

Features:

EUROLITE LED CLS-18 QCL RGB/WW 18x7W

LED floodlight with RGB/WW color mixing, barn doors, IR remote control and frost filter

- Additional frost filter provides a wide, soft and homogeneous light
- 3 buttons on the remote control for saving your own settings
- 18 powerful LEDs 7 W 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 11°
- With mounting bracket
- OLED display
- Very quiet working noise
- Preprogrammed in Light J; EASY SHOW 2; EASY SHOW 3
- Direct color temperature selection for 3100 preset values
- Rubber feet
- For application areas such as: Wedding/gala/events; stage; theater; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand knurled screw
- M4 thread
 - Package contents

Logistic

EAN / GTIN: 4026397733082 Weight: 40,50 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m Bulky product

ROADINGER Flightcase 4x LED CLS-18 QCL RGB/WW with wheels

Trunk case with castors

- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:

39,81 kg

EUROLITE LED CLS-18 QCL RGB/WW 18x7W

| Power supply: | 100-240 V AC, 50/60 Hz |
|-------------------------|---|
| Power consumption: | 104 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug included |
| Power output: | 1 x PowerCON (gray) |
| Fuse: | T 6,3 A fuse fix on board |
| Lamp type: | LED lamp |
| LED type: | 18 x 7 W 4in1 QCL RGB/WW (homogenous color mix) |
| Flash rate: | 1 - 23 Hz |
| DMX channels: | 3; 4; 6; 8; 11 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| | 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| | 1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control |
| Preprogrammed in: | Light J; EASY SHOW 2; EASY SHOW 3 |
| Projection: | Flicker-free |
| Beam angle: | 11° |
| Beam angle (1/2 peak): | 11° |
| · | Frost filter 15° |
| Beam angle (1/10 peak): | |
| Beam angle (1710 peak). | 26° |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Attachment system: Mounting bracket Display type: OLED display Transport aid: Rubber feet Dimensions: Length: 39,6 cm Width: 14,3 cm Height: 21,3 cm Weight: 4,75 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Mounting bracket Diameter mounting holes: Diameter mounting holes: 3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm Material: Metal, 2 mm Power cord Cable construction: Cable construction: 3 x 1,0 mm² H05VV-F Cable construction: 3 x 1,0 mm² H05VV-F Cable length: Approx. 1,2 m Frost filter Diameter mounting holes: 4 x Ø4,5mm Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,6 cm Height: 28,6 cm Knurled screw <th>Housing color:</th> <th>Black matte</th> | Housing color: | Black matte |
|---|--------------------------|--|
| Transport aid: Rubber feet Dimensions: Length: 39,6 cm Width: 14,3 cm Height: 21,3 cm Weight: 4,75 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Mounting bracket Diameter mounting holes: Diameter mounting holes: 3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm Material: Metal, 2 mm Power cord Cable construction: Cable construction: 3 x 1,0 mm² H05VV-F Cable length: Approx. 1,2 m Frost filter Diameter mounting holes: Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Bardoor Material: Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm | Attachment system: | Mounting bracket |
| Dimensions: Length: 39,6 cm Width: 14,3 cm Height: 21,3 cm Weight: 4,75 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Mounting bracket Diameter mounting holes: Diameter mounting holes: 3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm Material: Metal, 2 mm Power cord Cable construction: Cable construction: 3 x 1,0 mm² H05VV-F Cable length: Approx. 1,2 m Frost filter Diameter mounting holes: Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Bardoor Height: 28,5 cm Knurled screw Height: 28,5 cm Knurled screw M4 thread x 8 mm Legal specifications Special product: Special product: Not designed for household room illumination | Display type: | OLED display |
| Width: 14,3 cm Height: 21,3 cm Weight: 4,75 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Mounting bracket Diameter mounting holes: Diameter mounting holes: 3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm Material: Metal, 2 mm Power cord Cable construction: Cable construction: 3 x 1,0 mm² H05VV-F Cable length: Approx. 1,2 m Frost filter Diameter mounting holes: Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Material: Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: Special product: Not designed for household room illumination | Transport aid: | Rubber feet |
| Height: 21,3 cm Weight: 4,75 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Mounting bracket Diameter mounting holes: Diameter mounting holes: 3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm Material: Metal, 2 mm Power cord Cable construction: Cable construction: 3 x 1,0 mm² H05VV-F Cable length: Approx. 1,2 m Frost filter Diameter mounting holes: Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Bardoor Material: Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Specifications Specifications Not designed for household room illumination | Dimensions: | Length: 39,6 cm |
| Weight: 4,75 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Mounting bracket Diameter mounting holes: 3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm Material: Metal, 2 mm Power cord Cable construction: 3 x 1,0 mm² H05VV-F Cable construction: 3 x 1,0 mm² H05VV-F Cable length: Approx. 1,2 m Frost filter Diameter mounting holes: 4 x Ø4,5mm Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: Not designed for household room illumination | | |
| Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Mounting bracket Diameter mounting holes: 3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm Material: Metal, 2 mm Power cord Cable construction: 3 x 1,0 mm² H05VV-F Cable construction: 3 x 1,0 mm² H05VV-F Cable construction: Cable length: Approx. 1,2 m Frost filter Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: | | Height: 21,3 cm |
| sensitive environments) Mounting bracket Diameter mounting holes: 3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm Material: Metal, 2 mm Power cord Cable construction: Cable construction: 3 x 1,0 mm² H05VV-F Cable length: Approx. 1,2 m Frost filter Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: | Weight: | 4,75 kg |
| Diameter mounting holes: 3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm Material: Metal, 2 mm Power cord Cable construction: Cable construction: 3 x 1,0 mm² H05VV-F Cable length: Approx. 1,2 m Frost filter Diameter mounting holes: Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 1,6 cm Remote control Battery: Barndoor 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: Thread: M4 thread x 8 mm Legal specifications Special product: | Noise classification: | |
| Material: Metal, 2 mm Power cord | Mounting bracket | |
| Power cord Cable construction: 3 x 1,0 mm² H05VV-F Cable length: Approx. 1,2 m Frost filter Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: Not designed for household room illumination | Diameter mounting holes: | 3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm |
| Cable construction: 3 x 1,0 mm² H05VV-F Cable length: Approx. 1,2 m Frost filter Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Metal, 0,8 mm Dimensions: Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: | Material: | Metal, 2 mm |
| Cable length: Approx. 1,2 m Frost filter Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: | Power cord | |
| Frost filter Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: Not designed for household room illumination | Cable construction: | 3 x 1,0 mm² H05VV-F |
| Diameter mounting holes: 4 x Ø4,5mm Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: Not designed for household room illumination | Cable length: | Approx. 1,2 m |
| Material: Plastic, 2 mm Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: Not designed for household room illumination | Frost filter | |
| Dimensions: Width: 28,3 cm Height: 11,6 cm Remote control Ix button cell 3.0 V CR2032 lithium manganese built-in Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw M4 thread x 8 mm Legal specifications Special product: | Diameter mounting holes: | 4 x Ø4,5mm |
| Height: 11,6 cm Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Material: Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Height: 28,5 cm Knurled screw Thread: Thread: M4 thread x 8 mm Legal specifications Special product: | Material: | Plastic, 2 mm |
| Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw M4 thread x 8 mm Legal specifications Special product: | Dimensions: | Width: 28,3 cm |
| Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Barndoor Material: Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw M4 thread x 8 mm Legal specifications Special product: | | Height: 11,6 cm |
| built-in Barndoor Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: Not designed for household room illumination | Remote control | |
| Material: Metal, 0,8 mm Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: Not designed for household room illumination | Battery: | |
| Dimensions: Width: 46,5 cm Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: Not designed for household room illumination | Barndoor | |
| Height: 28,5 cm Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: Not designed for household room illumination | Material: | Metal, 0,8 mm |
| Knurled screw Thread: M4 thread x 8 mm Legal specifications Special product: Not designed for household room illumination | Dimensions: | Width: 46,5 cm |
| Thread: M4 thread x 8 mm Legal specifications Special product: Not designed for household room illumination | | Height: 28,5 cm |
| Legal specifications Special product: Not designed for household room illumination | Knurled screw | |
| Special product: Not designed for household room illumination | Thread: | M4 thread x 8 mm |
| | Legal specifications | |
| Intended use: Show effect lighting | Special product: | Not designed for household room illumination |
| | Intended use: | Show effect lighting |

ROADINGER Flightcase 4x LED CLS-18 QCL RGB/WW with wheels

| Aluminum profile frames: | 30 mm |
|--------------------------|-----------------------------------|
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes |
| Material: | Plywood multi-layer glued, 9 mm |
| Color: | Black, laminated |
| Device compartment: | 12 cm x 40 cm x 28 cm |
| Accessory compartment: | 11 cm x 46,5 cm x 28 cm |
| Dimensions: | Width: 87,5 cm |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo. Depth: 52,5 cm Height: 44 cm

Weight:

19,10 kg