



List price: 4758.81 €

incl. 19% VAT.

Features:

FUTURELIGHT DMB-100 LED Moving Head

PRO beam moving head with 100 W COB LED, 1° beam angle, gobo and color wheel, 2 prisms and QuickDMX port

- Bidirectional rotating 6-fold linear prism and 8-facet prism with variable speed, combinable for multi-facet effects
- 1 powerful LED 100 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 230° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; prism 8-fold; prism 6-fold linear; frost filter; focus motor-driven
- Color wheel with 14 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 17 gobos and open
shake effect
- Integrated show programs
- The device is cooled by temperature-controlled fan
- Control via DMX; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); RDM; sound to light via microphone
- Flicker-free
- With a beam angle of 1°
- With omega bracket
- Multicolor LCD display,
with battery buffering for easy controlling upgradeable
- Pulse-width modulation variable; dimmer curves with adjustable response; scenes user-definable; Dimmer speed (step response) adjustable
- Strobe effect
- Preprogrammed in Light Captain
- Rubber feet
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397709292

Weight: 62,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; rental
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x XLR cable, 2 x omega bracket

ROADINGER Flightcase 2x DMB-100 LED with wheels

Trunk case with castors, PRO version

- High-quality workmanship with birch multiplex 9,5 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 8 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover
- Branded hardware
- Made in Europe

Technical specifications:

Weight: 60,50 kg

FUTURELIGHT DMB-100 LED Moving Head

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Power output:	IP T-Con (F)
Fuse:	5 x 20 mm, T 3,15 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	230° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 16 Hz
Equipment:	Gobo wheel with static gobos; prism 8-fold; prism 6-fold linear; frost filter; focus motor-driven
Color generation:	Color wheel with 14 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 17 gobos and open Shake effect
DMX channels:	14; 16
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version

	5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	DMX; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); RDM; sound to light via microphone
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	1°
Beam angle (1/2 peak):	1°
Housing color:	Black
Attachment system:	2x omega bracket
Display type:	Multicolor LCD display battery buffering upgradeable
Transport aid:	Rubber feet
Dimensions:	Width: 33,0 cm Depth: 31,0 cm Height: 48,0 cm
Weight:	13,90 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x DMB-100 LED with wheels

Aluminum profile frames:	30 mm
Case handle:	8 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 9,5 mm
Color:	Black, laminated
Device compartment:	26,5 cm x 33 cm x 47 cm
Inside dimensions:	55,5 cm x 43 cm x 57 cm
Accessory compartment:	55,5 cm x 8,5 cm x 47 cm
Dimensions:	Width: 60 cm Depth: 48 cm Height: 74 cm
Weight:	27,65 kg; 27,65 kg