




8X



List price: 5353.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU IP Pixel Tube 360° PRO CRMX

Battery-powered IP pixel tube with RGB/CW/WW color mixing, 360° beam angle and CRMX receiver

- Integrated wireless receiver for CRMX operation
- Suitable for outdoor use IP65
- 144 powerful LEDs 0,5 W SMD 5050 5in1 PCL RGB/CW/WW (homogenous color mix)
24 segments controlled separately
- Battery operation up to 8,5h depending on program used
- Integrated automatic charging of the battery and status indicator
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend adjustable; color macros preset; white balance adjustable; program selection manual; running light automatic; background color adjustable; Emergency lighting function in case of power failure adjustable; Energy-saving mode
- Control via stand-alone; IR remote control; CRMX by LumenRadio
- DMX fail mode (hold; blackout; static; full on)
- With a beam angle of 360°
- Monochrome OLED display
- Charge status indicator
- Display of the remaining battery life for the current setting
- 3 buttons on the remote control for saving your own settings
- With pressure compensation membrane
- With holding clip
- With a KENSINGTON LOCK theft protection
- The device is cooled by passive convection cooling
- Application possibility: Standing; suspended
- Cordless, flexible and versatile
- 53 integrated show programs

Logistic

EAN / GTIN: 4026397748154

Weight: 65,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Direct color selection for 37 preset colors
- Preprogrammed in Light Captain; Colorchief
- Flicker-free
- Good color rendering index (CRI)

Package contents

- 1 x light effect, 1 x charger, 1 x power cord, 1 x remote control, 1 x battery, 1 x stand, 2 x fixation clip, 2 x splint, 1 x user manual, 1 x declaration of conformity, 1 x adapter

ROADINGER Flightcase 8x AKKU IP Pixel Tube 360° PRO CRMX with charging function and wheels

Trunk case

- Interior with foam padding
cover with foam padding
- Aluminum profile frames 35mm with rounded edges
- 4 hinged, chromium plated case handles
- Edge mounting handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover

Package contents

- 1 x case, 1 x power cord, 1 x user manual

Technical specifications:

Weight: 63,00 kg

EUROLITE AKKU IP Pixel Tube 360° PRO CRMX

Power supply:	100-240 V AC, 50/60 Hz 13V DC 3000 mA
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) power supply cord with AC unit (provided) Battery/battery pack
Cable construction:	2 x 0,75 mm² H03VVH2-F
Battery pack type:	1 x lithium ion 10,8 V, 9000 mAh, 97,2 Wh
Battery pack:	Battery operation up to 8,5h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	144 x 0,5 W SMD 5050 5in1 PCL RGB/CW/WW (homogenous color mix)
Flash rate:	2 - 20 Hz
DMX channels:	4; 5; 7; 14; 16; 20,1; 20,2; 22,1; 22,2; 24,1; 24,2; 120; 124
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; CRMX by LumenRadio
Preprogrammed in:	Light Captain; Colorchief
Projection:	Flicker-free

PWM frequency:	12600 Hz
Carrier frequency:	2,4 GHz
Modulation:	GFSK
DMX fail mode:	Hold; blackout; static; full on
Beam angle:	360°
Beam angle (1/2 peak):	360°
Beam angle (1/10 peak):	360°
Color rendering index (CRI):	84 Ra
Housing color:	Black matte
Attachment system:	2x holding clip M10 thread
Display type:	Monochrome OLED display
Display:	Charge status indicator , battery runtime calculation
Material:	Plastic; aluminum
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 109 cm Width: 7,0 cm Depth: 7,0 cm
Weight:	2,80 kg
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

ROADINGER Flightcase 8x AKKU IP Pixel Tube 360° PRO CRMX with charging function and wheels

Power supply:	100-240 V AC, 50/60 Hz
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Cable length:	1,2 m
Fuse:	5 x 20 mm, 5 A fuse replaceable
Aluminum profile frames:	35 mm
Case handle:	4 pc/pcs
Edge mounting handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Color:	Black, laminated
Device compartment:	7 cm x 109 cm x 10 cm
Accessory compartment:	113 cm x 9 cm x 21 cm
Material thickness:	9 mm
Dimensions:	Width: 119 cm Depth: 63 cm Height: 45 cm
Weight:	34,80 kg