eurolite®

EUROLITE BW-100 Bubble Machine

Compact, powerful bubble machine with wireless remote control

Art. No.: 51705124 GTIN: 4026397555042











List price: 106.98 €

incl. 19% VAT.

Features:

- Creates many hundreds of bubbles per minute
- High velocity fan makes bubbles rise quickly in the air
- Easy operation: simply fill in fluid and switch on!
- Low fluid consumption rate
- Standard and UV-active bubble fluids available as accessory
- Function switch on rear of unit
- Rugged metal housing
- Low power consumption
- Instantly ready for use without warm-up
- Output distance: Horizontal approx. 2,3 m
- Control via wireless remote control
- With mounting bracket
- For application areas such as: Wedding/gala/events; theater; restaurants, bars and hotels
- Very quiet working noise
- Application possibility: Standing; suspended
- Package contents
- 1 x device, 1 x user manual, 1 x external mains adapter, 1 x transmitter, 1 x declaration of conformity, 1 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x container, 1 x battery

Technical specifications:	
Power supply:	100-240 V AC, 50/60 Hz
	12V DC 1000 mA
Power consumption:	9 W

Logistic

EAN / GTIN: 4026397555042 Weight: 3,76 kg Length: 0.38 m Width: 0.25 m Heigth: 0.24 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Warm-up time:	0 sec
Output distance:	Horizontal approx. 2,3 m
Tank capacity:	0,7 l bubble fluid
Fluid consumption:	Approx. 10 ml/min
Control:	Wireless remote control
Attachment system:	Mounting bracket
Dimensions:	Width: 22 cm Depth: 34 cm Height: 24,5 cm
Weight:	3,48 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Remote control	
Battery:	1 x 12 V LR27 alkaline manganese built-in