

EUROLITE LED KLS Laser Bar FX AIR

Bar with 2 spots, 2 derbies, show laser, twinkle effect, AirW wireless system (2.4 GHz) and RF remote conferon (2.4 GHz) and RF remo





Art. No.: 51741099







List price: 570.01 €

incl. 19% VAT.

Features:

- Crossbar with integrated DMX control unit and stand sleeve
- Integrated AirW radio transceiver for wireless master/slave operation
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- When fog is used, this effect becomes especially attractive
- Dimmer electronic; color blend stepless; program selection; color change programs; color fade programs; running light programs; program speed adjustable
- Spot effect; laser; multi beam effect; strobe effect
- Integrated show programs
- Flicker-free
- Control via stand-alone; DMX; AirW; sound to light via microphone; master/slave function; wireless remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); wireless footswitch (optional)
- DMX fail mode (blackout; hold; full on; auto)
- The article is delivered with practical transport bag
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- The device is cooled by cooling fan
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Wedding/gala/events; party room; mobile use; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand
- Direct color selection
- Preprogrammed in Light Captain; Colorchief

Logistic

EAN / GTIN: 4026397740141

Weight: 9,20 kg Length: 1.15 m Width: 0.16 m Heigth: 0.42 m - AirW: operating range up to 70m

laser

 Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer

spotlight

- 3 powerful LEDs 8 W high-power 4in1 QCL RGB/WW (homogenous color mix)
2 spots controlled separately
- With a beam angle of 12°

light effect

- 4 powerful LEDs 3 W high-power R/G/B/W
- 14 powerful LEDs 0,2 W SMD 3535 3in1 TCL RGB (homogenous color mix)
2 spots controlled separately

remote control

- Operating range up to 30m

Package contents

1 x device, 1 x power cord, 1 x user manual, 1 x declaration of conformity, 1 x remote control, 2 x knurled screw, 2 x mounting bracket, 2 x washer, 1 x bag, 1 x battery

Technical specifications:

<u> </u>	
Power supply:	100-240 V AC, 50/60 Hz AC
Power consumption:	65 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable construction:	3 x 1,0 mm² H05VV-F
Cable length:	3 m
Power output:	1 x P-Con (gray), mounting version Bypass
Device fuse:	5 x 20 mm, T 1,6 A fuse replaceable
Fuse:	T 5 A fuse fix on board
Lamp type:	LED lamp
DMX channels:	3; 8; 11; 24; 27
DMX input:	1 x 3-pin XLR (M) mounting version 1 x USB, type A
DMX output:	1 x 3-pin XLR (F) mounting version Bypass
Cooling:	3 x cooling fan
Control:	Stand-alone; DMX; AirW; sound to light via microphone; master/slave function; wireless remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); wireless footswitch (optional)
Preprogrammed in:	Light Captain; Colorchief
Projection:	Flicker-free
Range:	AirW: range up to 70m
Carrier frequency:	2,4 GHz
DMX fail mode:	Blackout; hold; full on; auto
Color temperature:	3100K; 5300K
Distance to wall:	500 mm
Housing color:	Black matte

Attachment system:	Tube: Ø 35mm 2x mounting bracket
Display type:	Monochrome 4 digit 7-segment LED display
USB port:	1 x type A
Diameter mounting holes:	2 x Ø6mm
Use of brands:	Built with SEETRONIC connector
Material:	Metal, painted
Dimensions:	Length: 103 cm Depth: 8,2 cm Height: 33,6 cm
Weight:	8,10 kg
Noise classification:	Class 2 (slight noise)
Remote control	
Battery:	1 x 12 V 23AE alkaline manganese built-in
Range:	Range up to 30m
Carrier frequency:	433,92 MHz
Laser	
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
Light effect	
LED type:	4 x 3 W high-power R/G/B/W 14 x 0,2 W SMD 3535 3in1 TCL RGB (homogenous color mix)
Spotlight	
LED type:	3 x 8 W high-power 4in1 QCL RGB/WW (homogenous color mix)
Beam angle:	12°
Beam angle (1/2 peak):	Spot 12° multicolor
Beam angle (1/10 peak):	Spot 30°