

## EUROLITE LED WF-100 Water Effect

LED projection effect for water reflections with color wheel & DMX

Art. No.: 51918547

GTIN: 4026397737646



**List price: 355.81 €**

incl. 19% VAT.

### Features:

- 1 powerful LED 100 W COB (chip-on-board) cold white (CW)
- Animation wheel; focus manual
- Dimmer; color change adjustable; Rotation speed stepless
- Water effect; strobe effect
- Color wheel with 5 dichroic filters plus open half colors selectable, Rainbow effect with adjustable speed in both directions
- 8 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone
- Flicker-free
- DMX fail mode (hold; blackout)
- With a beam angle of 45°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels
- Application possibility: Suspended; on stand
- 4 rubber feet
- Preprogrammed in Light´J; Light Captain

#### Package contents

- 1 x light effect, 1 x user manual, 1 x power cord

### Logistic

EAN / GTIN: 4026397737646

Weight: 5,50 kg

Length: 0.41 m

Width: 0.33 m

Height: 0.22 m

## Technical specifications:

|                          |                                                                                                                                                                           |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                                                    |
| Power consumption:       | 140 W                                                                                                                                                                     |
| IP classification:       | IP20                                                                                                                                                                      |
| Protection class:        | Protection class I                                                                                                                                                        |
| Power connection:        | Mains input via P-Con (blue), mounting version power supply cord with safety plug                                                                                         |
| Cable construction:      | 3 x 1,0 mm <sup>2</sup> H05VV-F                                                                                                                                           |
| Cable length:            | 1,45 m                                                                                                                                                                    |
| Power output:            | P-Con (gray), mounting version                                                                                                                                            |
| Fuse:                    | 5 x 20 mm, T 2 A fuse replaceable                                                                                                                                         |
| Lamp type:               | LED lamp                                                                                                                                                                  |
| LED type:                | 1 x 100 W COB (chip-on-board) cold white (CW)                                                                                                                             |
| Flash rate:              | 0 - 30 Hz                                                                                                                                                                 |
| Equipment:               | Animation wheel; focus manual                                                                                                                                             |
| Color generation:        | Color wheel with 5 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions                                             |
| DMX channels:            | 5                                                                                                                                                                         |
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                                            |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                                            |
| Cooling:                 | 3 x temperature-controlled fan                                                                                                                                            |
| Control:                 | QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone |
| Preprogrammed in:        | Light´J; Light Captain                                                                                                                                                    |
| Projection:              | Flicker-free                                                                                                                                                              |
| DMX fail mode:           | Hold; blackout                                                                                                                                                            |
| Beam angle:              | 45°                                                                                                                                                                       |
| Housing color:           | Black                                                                                                                                                                     |
| Attachment system:       | Mounting bracket                                                                                                                                                          |
| Display type:            | 4 digit 7-segment LED display                                                                                                                                             |
| USB port:                | Type A                                                                                                                                                                    |
| Transport aid:           | 4 x rubber feet                                                                                                                                                           |
| Diameter mounting holes: | 3 x Ø12mm                                                                                                                                                                 |
| Material:                | Metal                                                                                                                                                                     |
| Dimensions:              | Width: 32,0 cm<br>Depth: 23,5 cm<br>Height: 19,5 cm                                                                                                                       |
| Weight:                  | 4,75 kg                                                                                                                                                                   |
| Noise classification:    | Class 2 (slight noise) depending on mode used                                                                                                                             |
| Legal specifications     |                                                                                                                                                                           |
| Special product:         | Not designed for household room illumination                                                                                                                              |

Intended use:

Show effect lighting