

OMNITRONIC ODP-208T Altoparlante da installazione 100V bianco

Weather-proof 8" wall speaker (IP65) with mount, 150 W RMS

Art.n.: 11036961

GTIN: 4026397723007



Prezzo di listino: 320.11 €

incl. 19% IVA

Descrizione :

Great sound - also runs with 100 volts

You want reliable and balanced sound for your bar, restaurant, shop or the conference area of your hotel? You need indoor and outdoor speakers? With the OPD series you get powerful installation speakers that meets all your requirements.

The speakers have a brilliant sound pattern and are available in a low ohm (16 ohms) and in a 100 V version. These two cover both small and large installations. A rotatable mounting bracket is included in the delivery. A swivel wall mount with matching colors is optionally available.

With their weatherproofed (IP65) plastic cabinet the ODP speakers are well prepared for outdoor use, indoor use is of course also possible.

Features :

- Sistema a 2 vie con woofer da 20 cm (8") e tweeter a cupola da 2,5 cm (1")
- Stabile custodia in plastica con griglia in metallo
- Commutatore di potenza con posizione di funzionamento a 16 Ohm
- Morsetti a vite per un comodo collegamento
- Con staffa di montaggio
- Adatto per uso esterno IP65
- Per campi di applicazione come, ad esempio,: Allestimenti per fiere e negozi; Ristoranti, bar e hotel; Presentazioni e conferenze sui prodotti

Dotazione della fornitura

- 1 x Manuale d'uso, 1 x testata, 1 x Staffa di montaggio, 6 x viti, 1 x Occhiello per corda di sicurezza, 1 x Coperchio, 2 x Rondella, 1 x chiusura a vite, 1 x morsetto a vite

Logistica

EAN / GTIN: 4026397723007

Peso : 12,15 kg

Lunghezza : 0.36 m

Larghezza : 0.30 m

Altezza : 0.50 m

Dati tecnici :

Grado di protezione:	IP65
Capacità di carico:	Programma: 300W Nominale: 150W RMS
Intervallo di frequenza:	60 - 18000 Hz
Sensibilità:	94 dB (1W/1m)
Pressione acustica massima:	116 dB
Direzionalità:	90° x 50°
Impedenza:	ELA tecnica 100 V; 16 Ohm
Sistema di registrazione:	Staffa di montaggio
Alimentazione di derivazione:	37,5W; 70W; 150W RMS via selettore switchable
Collegamenti:	Ingresso: Altoparlante via terminale a vite
Frequenza di taglio:	2300 Hz
Altoparlante:	1 x 8" Woofer 2" woofer a bobina mobile 1 x 1" tweeter a cupola 1" tweeter a cupola a bobina mobile
Tipo di altoparlante:	Cassa compatta; altoparlante in superficie (parete/soffitto)
Colore:	Bianco
Misure:	Larghezza: 24,1 cm Profondità: 28,5 cm Altezza: 45 cm
Peso:	10,90 kg