

## OMNITRONIC MAXX-1508 Top a 2 vie 2x

2 diffusori full range passivo da 8", 150 W RMS

Art.n.: 11038833

GTIN: 4026397658064



## L'articolo non è più disponibile.

### Descrizione :

The MAXX-1508DSP is an active 2.1 PA system with 700 watts output power. It provides perfect sound and good level stability in various kinds of mobile PA applications.

The high-power 15" subwoofer with power-efficient Class D amplifier in a bass reflex cabinet delivers powerful, dry bass. The two satellite loudspeakers with 8" bass/midrange drivers and 1" compression drivers are equipped with a passive 2-way crossover including PTC tweeter protection and ensure a well-rounded sound experience.

Equipped with a DSP (digital signal processor) which enables convenient application presets for quick sound contouring, the MAXX-1508DSP offers combined XLR and 6.3 mm inputs with XLR parallel output (for linking additional systems), and an additional RCA input with level adjustment. Enjoy music wirelessly from your smartphone or any other Bluetooth device via the integrated Bluetooth audio receiver and charge them at the same time via the integrated powerbank.

The MAXX-1508DSP subwoofer's professional hardware includes a rugged multiplex/MDF enclosure, scratch-resistant lacquer, steel grille and ergonomically shaped handles. Swivel castors for easy transport are optionally available. Matching speaker stands, distance tubes, and stand forks are also available as accessories.

### Features :

- Sistema Bass reflex a 2 vie con woofer da 8" e driver a compressione da 1"
- Formano un potente sistema 2.1 con il subwoofer MAXX-1508
- Con crossover passivo a 2 vie con protezione del tweeter PTC
- Nero Metallo grille with Schiuma acustica
- Possibilità di utilizzo: Verticale; volante; monitoring; su treppiede

### Logistica

EAN / GTIN: 4026397658064

Peso : 18,35 kg

Lunghezza : 0.53 m

Larghezza : 0.32 m

Altezza : 0.48 m

- Con punti di ancoraggio
- Maniglia di trasporto robusta
- Per campi di applicazione come, ad esempio,: DJ mobili/Intrattenitori solisti; noleggiatore; Uso mobile

#### **Dotazione della fornitura**

- 2 x testata, 2 x cavi per altoparlanti

#### **Dati tecnici :**

Capacità di carico:	Programma: 300W Nominale: 150W RMS
Intervallo di frequenza:	120 - 18000 Hz
Sensibilità:	92 dB
Pressione acustica massima:	116 dB
Direzionalità:	90° x 60°
Impedenza:	4 Ohm
Punti di ancoraggio:	5 x Filettatura M8
Collegamenti:	Ingresso: Altoparlante via 1 x Presa da incasso per altoparlanti (F)
Altoparlante:	1 x 8" Woofer 1 x 1" tweeter con driver a compressione
Tipo di altoparlante:	Cassa compatta
Maniglia di trasporto:	1 Pezzo
Materiale:	MDF (pannello di fibra a media densità), 16 mm
Misure:	Larghezza: 25,5 cm Profondità: 24,1 cm Altezza: 42,1 cm
Peso:	17,25 kg