

## FUTURELIGHT EYE-60 LED Moving-Head Wash

Moving head wash with 3 W RGBW LEDs

Art.n.: 51841337

GTIN: 4026397391114



**L'articolo non è più disponibile.**

### Features :

- Equipped with 60 x 3 W LEDs: 22 x red, 17 x green, 15 x blue, 6 x white
- Correction of the color temperature via 6 cold white LEDs possible
- Long LED life
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Software-upload by optional FUTURELIGHT ULB-1 upload box via DMX link (from software version 2.0, 06/2010)
- Sound-controlled via built-in microphone
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN angle switchable between 630° and 540°
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Stepless RGBW color changing
- Programmable color-change speed and strobe effect
- Random strobe effect
- Lightbeam with 22° radiation angle
- Blue LCD display
- ESDC function (Easy Service Data Check) with battery-buffered Control Board for operation time readouts etc.
- Strobe effect with 1-25 flashes per second
- Masterdimmer
- Rainbow effect

### Logistica

EAN / GTIN: 4026397391114

Peso : 9,45 kg

Lunghezza : 0.36 m

Larghezza : 0.30 m

Altezza : 0.44 m

- Control Board with LCD display and foil-keyboard for adjusting the DMX starting address, PAN/TILT Reverse, Program, Reset
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- DMX control via every standard DMX controller
- Controllabile via controllo della musica via microfono; RDM

#### **Dispositivo**

- Senza fili, flessibile e versatile

#### **Dotazione della fornitura**

- 1 x Dispositivo

### **Dati tecnici :**

|   |   |
|---|---|
| Alimentazione elettrica:                    | 100-240 V AC, 50/60 Hz                                      |
| Potenza totale installata:                  | 250 W   |
| Movimento oscillatorio TILT massimo:        | 265° posizionamento   |
| Movimento di rotazione PAN massimo:         | 630° posizionamento   |
| Frequenza di lampeggiamento:                | 1 - 25 Hz   |
| Canali DMX:                                 | 13  |
| Attivazione:                                | Controllo della musica via microfono; RDM                   |
| Angolazione del fascio di luce (1/2 picco): | 22°   |
| Misure:                                     | Larghezza: 31 cm<br>Profondità: 28,5 cm<br>Altezza: 38,5 cm |
| Peso:                                       | 8 kg  |
| <b>Dispositivo</b>                          |   |
| Tipo di batteria:                           | 1 x Ioni di litio 7,4 V, 2,24 Wh                            |
| DMX channels:                               | 13  |
| DMX connection:                             | 3-pin XLR   |
| Flash-rate:                                 | 25 Hz   |
| Maximum PAN-movement 630°:                  | in 2.5 s  |
| Maximum TILT-movement 265°:                 | in 1.5 s  |
| LED number:                                 | 60  |
| Beam angle:                                 | 22°   |
| Dimensions (L x W x H):                     | 310 x 285 x 385 mm  |
| <b>Specifiche legali</b>                    |   |
| Prodotto speciale:                          | Non destinato all'illuminazione di ambienti domestici       |
| Destinazione d'uso:                         | Illuminazione per effetti speciali                          |