

## ALUTRUSS DECOLOCK DQ3-2000 Traversa a 3 punti

Sistema di trave universale a 3 punti in struttura leggera

Art.n.: 60301616

GTIN: 4026397209860



**Prezzo di listino: 213.01 €**

incl. 19% IVA

### Descrizione :

DECOLOCK DQ3 3-point truss system

DECOLOCK DQ3 is a 3-point truss system made of aluminum. The individual elements are connected via three cones, pivots and pins.

The advantage of the conical connection system is that the cones completely fit into the main chords so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

The three main chords are made of 35 mm aluminum tube with 2 mm wall thickness and offer sufficient strength at a low weight. The braces have a diameter of 10 mm with 2 mm wall thickness and provide the system with a decorative appearance.

With DECOLOCK, you can realize compact installations with low self weight, e. g. for shop displays, shop decorations, exhibitions, interior design, fair booths, discotheques and theatres.

DECOLOCK is primarily designed for decorative installations and can be used for permanent or temporary installations due to its highly aesthetic appearance. The advantages of this system are the compact construction with 220 and 195 mm outer dimensions, low weight, optimum strength along with easy and quick assembly.

The documentation of this truss system is closely related to the Codes of Practice SQ P1 - Truss Systems published by the VPLT/PLASA. The load table as calculation base can be downloaded from the Internet before buying the product!

### Logistica

EAN / GTIN: 4026397209860

Peso : 5,32 kg

Lunghezza : 2.00 m

Larghezza : 0.26 m

Altezza : 0.23 m

Merci voluminose

## Features :

---

- La lega di alluminio per un look classico e high-tech
  - Montaggio rapido, efficiente e affidabile tramite connettori a cono QUICK-LOCK
  - Un'ampia selezione di lunghezze, elementi circolari e angolari offre la massima flessibilità
  - Costruzioni speciali secondo le specifiche del cliente su richiesta
  - Tubo della cinghia: 35 mm
  - Disponibile su richiesta in qualsiasi colore RAL
  - Disponibile in vari modelli
  - Certificato TÜV Süd
  - Per campi di applicazione come, ad esempio,: Teatro; Allestimenti per fiere e negozi; installazione; palco
  - Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica
- Dotazione della fornitura**
- 1 x set di connettori

## Dati tecnici :

---

|                                  |   |
|----------------------------------|---|
| Tubo della cinghia:              | 35 mm x 2 mm  |
| Processo di saldatura:           | Impulso TIG   |
| Materiale di saldatura:          | AlMg 5  |
| Colore:                          | Color alluminio; disponibile su richiesta in qualsiasi colore RAL |
| Spessore x diametro del puntone: | 10 x 2mm  |
| Misure:                          | Lunghezza: 200 cm<br>Larghezza: 22 cm<br>Altezza: 19,50 cm        |
| Peso:                            | 4,61 kg   |